

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representation of
The original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

FIG. 1




FIG. 1

FIG. 2




FIG. 2




FIG. 3a




FIG. 3b





FIG. 3c








FIG. 6




FIG. 7




FIG. 9




FIG. 10




FIG. 12






FIG. 15




FIG. 16




FIG. 17




FIG. 17A




FIG. 20




FIG. 21




FIG. 22




FIG. 23a




FIG. 23b




Fig. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31





FIG. 32






FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57






Fig. 58






FIG. 61

FIG. 62




FIG. 62




FIG. 63




FIG. 64




FIG. 65




FIG. 66




FIG. 67




FIG. 68




FIG. 69




FIG. 70




FIG. 71




FIG. 72




FIG. 73




FIG. 74




FIG. 75




FIG. 76




FIG. 77




FIG. 78




FIG. 79




FIG. 80




FIG. 81




FIG. 82




FIG. 83




FIG. 84




FIG. 85




FIG. 86





FIG. 87



Vitrinite Reflectance (%)

FIG. 88




FIG. 89




FIG. 90




FIG. 91

FIG. 92




FIG. 92




FIG. 93

FIG. 93




FIG. 94

FIG. 95




FIG. 95




FIG. 96




FIG. 97




FIG. 98



FIG. 99

FIG. 100




FIG. 100




FIG. 101

FIG. 102




FIG. 102




FIG. 103




FIG. 104




FIG. 105

FIG. 106 is a graph showing the Ethene/Ethane Ratio versus the temperature change rate in °C/day. The Y-axis represents the Ethene/Ethane Ratio from 0% to 20% in 2% increments. The X-axis represents the temperature change rate from 1 to 100,000 °C/day on a logarithmic scale. Data points are plotted as solid diamonds.




FIG. 106




FIG. 107




FIG. 108




FIG. 109

FIG. 110




FIG. 110




FIG. 111

FIG. 112




FIG. 112




FIG. 113

FIG. 114





FIG. 114

A scatter plot showing Flow Rate (Y-axis) versus Time (X-axis) for two series, 3940 and 3942. The Y-axis ranges from 0 to 8.495 with major ticks every 1.416. The X-axis ranges from 0 to 16.99 with major ticks every 2.832. Series 3940 is represented by square markers and Series 3942 by diamond markers. Both series show a similar trend, starting at a flow rate of approximately 1.416 at time 0, remaining relatively constant until about 2.832, then increasing sharply to a peak of approximately 7.079 at time 14.16, before decreasing to approximately 5.663 at time 16.99.

Time	Flow Rate (3940)	Flow Rate (3942)
0	1.416	1.416
2.832	1.416	1.416
5.663	5.663	5.663
8.495	7.079	7.079
11.326	7.079	7.079
14.157	5.663	5.663
16.988	1.416	1.416

Methane Injection Rate (m^3/hr)

FIG. 115



Methane Injection Rate (m³/hr)

FIG. 115





FIG. 116



■ 3960 ▲ 3962 ◆ 3964 × 3966 * 3968 • 3969

FIG. 117




FIG. 118

Figure 1 is a line graph showing the mole percentage of various components over time (t in days) for a polymerization process. The y-axis is labeled "Mole %" and ranges from 0 to 90. The x-axis is labeled "t(days)" and ranges from 0 to 300. The graph shows several curves representing different components. Key peaks are labeled with their corresponding mole percentages: 3980, 3982, 3984, 3986, and 3988. The curves show a general increase in mole percentage over time, with some components showing more rapid growth than others.




FIG. 120




FIG. 122




FIG. 123




FIG. 124




FIG. 125




FIG. 126




FIG. 127




FIG. 128




FIG. 129




FIG. 130

Flow rate (Mm³/day) vs. time (days) for two different flow rates (5060 and 5070 Mm³/day) over a period of 3800 days. The graph shows a sharp increase in flow rate around day 2400, followed by a gradual decline.




FIG. 131




FIG. 132

Flow rate (Mm³/day) vs. time (days)




FIG. 134

time (days)	Bm^3
0	0
500	.047
1000	.094
1500	.142
2000	.189
2500	.236
3000	.283
3500	.330
4000	.566
4500	.545

FIG. 135